

NICKLOS DRILLING COMPANY

RIG 3

DRAWWORKS: OIME SL-5, Grooved for 1-1/8" drill line, Powered by 3 Caterpillar D3408 TA engines with Allison CLT6061 transmissions, 425 HP each.

BRAKE: Parkersburg 46" Single Rotor Hydromatic Brake

MAST: Parco 131' Mast, 550,000 lb. Static Hook Load, 6 Sheave Crown Block

SUBSTRUCTURE: Parco 18.5' Split Level Substructure, 467,000 lb. Rotary Capacity with 357,000 lb simultaneous Set Back

PUMPS: 2- Ideco T1000, 1,000 HP Triplex Mud Pumps, one powered by Caterpillar D-398 TA Diesel Engine with National C300-64-FH TC and one from the compound.

MUD SYSTEM: 2 Tank Mud System, 750 bbls. Shaker Tank complete with (2) 6" x 8" Centrifugal Pumps Powered by 75 hp Electric Motors, SWACO 12 Cone Desilter, 2 Cone Desander and Vacuum Degasser, with 2 Derrick AWD Linear Motion Shale Shakers. Suction tank with 2 - 6" x 8" Centrifugal Pumps Powered by 75 hp Electric Motors, Mud Hopper, 4 - Agitators

ROTARY: National 27-1/2" Rotary Table

TRAVELING EQUIPMENT: Gardner Denver TB-300 Block with BJ 6250 Unimatic 250 ton Hook, National N69 300 ton Swivel

ELECTRICAL SYSTEM: 2 - 460 KW Caterpillar Generators Model SR4 Powered by 2 - Caterpillar D-3412TA Diesel Engines

BLOWOUT PREVENTERS Hydril GL 13-5/8" 5,000 psi Annular Blowout Preventer, 1 Cameron 13-5/8" 10,000 psi U Double Ram Preventer, 3" x 2" Choke Manifold, Valcon 6 Station 80 gal. Accumulator with Remote Panel, Atmospheric Degasser

AUXILIARY EQUIPMENT: Satellite Automatic Driller, 4-Pen Recorder, 2 - Ingersoll Rand Air Hoists, Foster Kelly Spinner, Varco DP Spinner Wrench

DRILL STRING: 5" OD 19.50 lb. Drill Pipe, 18 - 6-1/2" OD Drill Collars, 9 - 8" OD Drill Collars

700 Louisiana Suite 3910, Houston, Texas 77002
713-224-5959, 713-224-5993 fax, www.nicklosdrilling.com